

Model / Features	Control up to	Card Storage	Events transaction	Time sets (3 intervals each)	TimeZone (7 days+2 holidays / time zone)	User accessibility
CENTURION CAS-1S	1 door	2,500	2,500	50	50	50
S-SERIES CAS-2S / 4S / 8S	2/4/8 door	5000	2,500	100	100	100
ADVANCED-SERIES CAS-12S	12 doors	5,000	50,000	256	256	256
CAS-16S	16 doors	5,000	50,000	256	256	256

Ordering Information

Controller (S-Series)

	Stock code	Description
	CAS-2S	2-doors controller
	CAS-4S	4-doors controller
	CAS-8S	8-doors controller


Dimension
194mm(W) x 291mm(H) x 81mm(D)

(Advanced Series)

	Stock code	Description
	CAS-12S	12-doors controller
	CAS-16S	16-doors controller

Dimension
194mm(W) x 291mm(H) x 81mm(D)

Reader

	Stock code	Description
	PRO-NDT	Proximity reader c/w 12 keys polycarbonate keypad reader interface unit & ABS casing with blue LCD (Format : Magnetic Signal)
	PRO-NDH	HID proximity reader c/w 12 keys polycarbonate keypad, reader interface unit ABS casing with blue LCD. (Format : Wiegand 26 bits)
	CAS-MSN26	Contact-less smart card reader (Mifare Card Serial Number) c/w 12 keys polycarbonate keypad, reader interface unit & ABS casing with blue LCD (Format : Wiegand 26 bits)
	PRO-4SM-T	Proximity reader c/w 12 keys polycarbonate keypad, reader interface unit & metal casing.(Format : Magnetic Signal)

Dimensions :
170H x 185W x 35D mm

Recommended Accessories

Stock code	Description
CPC30	3A/13.8Vdc power supply unit with battery charger
CLP-22-2W	RS485 lightning / surge arrestor (2 wires)
600LB	12Vdc,600lbs electric magnetic lock
Bat7	7AH sealed lead acid rechargeable battery
Communication Cable	Belden 1419

For a full accomplishment of CE marking for door access system, the recommended accessories on the above item need to be included.